Energy products

Vent valve

C327345, C327785

Three-inch flange, 24 or 125 vdc, solenoid-pilot actuated (SPA)



Meggitt's three-inch sleeve style gas vent valve is in use on many aero-derivative industrial gas turbines. With millions of field operating hours, this design continues to prove the high reliability of Meggitt technology.

Specifications

Function: Hot gas vent for aero-derivative turbine engines

Type: Normally closed (fail closed), solenoid-pilot actuated, two or three inch,

elbow, sleeve valve, 24 or 125 VDC

Physical size: 7.5" wide, 25" high

Weight: 83 pounds

Flange type: 3.0" ANSI B16.5 CL 600 raised face flanges

Line pressure: 0 to 500 psig

Actuation pressure: 80 to 125 psig

Fluid temperature: 32 to 1100°F (bleed air)

Ambient temperature: -20 to 240°F

Heat soak: 400°F maximum ambient, 1 to 2 hours, de-energized

Performance:

Flow: 1.2 pounds/sec compressor bleed air

Pressure drop: 0.70 psid maximum at all normal operation conditions

Internal leakage: 0.00025 pound/minute maximum

Operating time: 1 second full stroke response, opening or closing

Electrical:

Solenoid: Continuous duty, 24 VDC nominal (18 to 30 VDC), 1.92 amperes

maximum or 125 VDC (95 to 140 VDC), 0.43 ampere maximum

Position indicating switch: 125 VDC, 3-wire, SPDT

Key features

- Fail-safe closed (de-energized)
- Open and closed position indicating switch circuits
- 1 second full stroke response time (opening or closing)
- Supplied with mounting kit
- Used on both DLE and SAC turbine engines
- Non incendiary design, CE-ATEX and PED certified
- All stainless steel valve and body materials for NACE compliance
- No maintenance required under normal conditions

Meggitt Control Systems








Energy products

Purge valve

C327345, C327785

Key dimensions



Contact

Meggitt Controls

12838 Saticoy St North Hollywood California 91605-3505 USA

Telephone: (818) 765-8160 FAX: (818) 759-2194

www.meggitt.com

Meggitt Control Systems

